

QUICK



AND EASY

1 NOVEMBER - 31 DECEMBER 2022

630A

NEXT LEVEL GREASING



- Grease pressures of up to 7,250psi (500bar)
- Adjustable delivery rates of 160g/min (high) or 100g/min (low)
- Able to dispense up to 16 cartridges before battery recharge is required
- Backlit display provides real time battery level, grease level and grease dispensed feedback information
- Lightweight and ergonomical

430A also available \$784.00

\$689.00

FOC

20033 LED Cordless & Rechargeable Pocket Work Light

WITH EACH PURCHASE OF THE 630A
NOV 1 - DEC 31 2022
WHILE STOCKS LAST

QUOTE CODE 630APLOFFER
TO TAKE ADVANTAGE



SCAN ME



428262
Samoa 180kg
Air Operated Grease Kit

- 55:1 ratio grease pump develops up to 7,950psi (548bar)
- Integral filter eliminates the chance of pump tube contamination
- Lightweight ergonomic, cast alloy, grease control valve included
- Grease control valve has single shot or continuous flow option
- Ideal for busy workshops where greasing is undertaken all day, every day
- 180kg drum not included

\$2,026.00 



660AN
Alemlube Trigger Action
Grease Gun

- Grease pressures of up to 8,500psi (586bar)
- Delivers up to 1.1g of grease per stroke
- Twin Lock System seals the piston and eliminates the possibility of dummy lubrication
- Ever-Flow System enables the gun to be used with thick tacky greases even in the coldest conditions
- High volume / high pressure option facilitates fast and efficient greasing
- Manufactured in Germany

\$138.60



G10010N
Alemlube EL Series
Trigger Action Grease Gun

- Grease pressures of up to 4,000psi (276bar)
 - Delivery rates of up to 1.15g per stroke
 - Robust die cast aluminium head assembly
 - Heavy duty 4 jaw coupler
 - Exceptional value for money for cost conscious customers
- G10020N** also available in but lever action **\$48.80**

\$70.70



600A
Alemlube Lever Action
Grease Gun

- Grease pressures of up to 12,000psi (828bar)
- Delivers up to 1.6g of grease per stroke
- 450g capacity
- Suitable for all grease grades up to NLGI3
- Twin Lock System seals the piston and eliminates the possibility of dummy lubrication
- Ever-Flow System enables the use of thick/tacky greases

\$101.70



424170
Samoa 20kg Grease Kit

- Delivery rates of up to 0.9kg/min
- 55:1 ratio air motor develops grease pressures of up to 7,950psi (548bar)
- Will handle high density, tacky greases up to NLGI2
- Supplied with a 4m long hose assembly enabling quicker and easier greasing of your plant and equipment
- Heavy duty 3 jaw coupler ensures a tight and precise grease nipple connection
- Manufactured in Spain

424150 also available with trolley
\$1,496.00

\$1,334.00



KPL-24EX
Alemlube 24V 20kg
Grease Kit

- A unique product, this 24V, 20kg grease pump kit is ideal for mining & heavy industrial applications
- Suitable for grease up to NLGI2
- Working pressure of 4,000psi (276bar)
- Continuous operation
- Dispenses up to 70-80g/min
- Suitable for working temperatures of -10°C to +40°C
- Can be used with a hose reel inclusive of up to 15m of hose

EPL-240SP also available in 240V
\$7,055.00

\$6,782.00



ALEMITE 7785-A5 180KG GREASE PUMP

The Alemite 7785-A5 180kg Grease Pump is a heavy duty high volume pump ideally suited to demanding operations in mine sites, contractor workshops & installations and mobile service vehicles where hazardous and demanding conditions exist.

The 7785-A5 can deliver hard to pump fluids and viscous lubricants up to NLGI #3. Built for continuous duty, the 7785-A5 double acting pump is consistent, reliable, and maintains pressure over long distances.

PULSARLUBE E SERIES ELECTRO-CHEMICAL GAS DRIVEN GREASE LUBRICATORS

Pulsarlube E Series Electro-Chemical Gas Driven Grease Lubricators are one of the most popular & widely used in all industrial applications. The safe & environmentally friendly Nitrogen Gas (N₂) Generation system is a reliable and steady dispensing mechanism which makes the E series unique in the market. Nitrogen Gas Generation E series are stable & not affected by any ambient temperature variations & are simple & easy to operate via a Mode Selector Switch with instant on/off options.

E Series are intrinsically safe with IECEx & ATEX EXD Explosion-proof certification for use within any hazardous area. E Series are available with capacities of 60, 120 & 240cc, provide low cost lubrication solutions and can be installed in any confined area. Complete with IP68 protection class these lubricators are suitable for use in dusty environments such as Quarries, Brick Plants, Mining etc. Empty E Series lubricators can be custom filled on site using a grease gun.





14512
Alemlube Quick Release Grease Gun Coupler

- Works with all grease gun types - pneumatic, manual and battery
- 1/8" BSP(f) thread
- Maximum working pressure of 10,000psi (690 bar)
- 90mm long

A14512 also available in packaging \$42.50

14511 also available - 1/8" NPT(f) thread \$50.30

14510 also available - 1/8" BSP(f) thread & 135mm long \$61.30

\$40.90



G10040N
Alemlube EL Series 18V Lithium-ion Cordless Grease Gun

- Generates grease pressures of up to 10,000psi (690bar)
- Capable of delivering up to 80g/min
- 25 minutes continuous working time
- Supplied with two batteries, 3,000 mAh & 1,500 mAh
- Recharge time of 75 minutes (1,500 mAh battery)
- Dispenses grease from up to 12 x 450g cartridges before changing over or recharging of the 3,000 mAh battery is required

\$574.00



G10042
Alemlube EL Series 14.4V NiCad Battery Cordless Grease Gun

- Heavy duty carry case supplied standard
- Light weight at just 2.1kg
- Battery capacity: 14.4 NiCad battery 1500 mAh
- High pressure delivery: 7500psi (517bar)
- High flow rate of 74cc/min
- 1 x 1 hour quick charger
- 2 x 1500 mAh battery packs

\$380.00



670AN5
Alemlube 20V Lithium-ion Cordless Grease Gun

- Delivery rates of up to 170g/min (high) & 113g/min (low)
- Grease pressures of up to 10,000psi (690bar)
- Up to 35 cartridges per battery charge
- Built in Intelligence
- LCD with real time battery capacity, grease level and grease metering information
- Supplied with two batteries, 4.0Ah and 2.5Ah
- Impact resistant LCD lens surrounded by impact absorbing bezel

\$1,429.00



G100120
Alemlube EL Series 20kg Grease Kit

- Effortless greasing
- Heavy duty grease control valve
- 4m long hose assembly
- Affordable and robust
- Maximum fluid pressure of 5,800psi (400bar)
- All types of grease up to NLGI2
- Delivers up to 600g/min
- Tested to up to 24,000kg
- Air consumption of 3.6cfm at 150psi to 150psi (10bar)

\$875.00



ALEMLUBE
Grease Nipple Assortment Kits

All grease nipples included in the kit are case hardened, fully chromated, zinc passivated, batch tested to 8,000psi (552bar) and conform to international standards including BSS 1486, DIN 71412, SAE J534 and JIS B1575

- Manufactured in the UK

- L4674 101 Agricultural grease nipple assortment kit \$104.00
- L4675 101 Industrial grease nipple assortment kit \$100.90
- L4676 100 Metric grease nipple assortment kit \$91.00



RAVAGLIOLI 25t RAV825.10 COMMERCIAL VEHICLE KNUCKLE LIFT

The RAV825.10 25t Commercial Vehicle Knuckle Lift that makes light work of heavy lifting. No cross rails or torsion bars between lifting platforms maximises accessibility in the working area facilitating greater workflow and productivity. Manufactured with a mechanical locking device with automatic engagement and pneumatic release, the RAV825-10 ensures maximum safety for workshop technicians when the lift is in standing position.

All pivot points are fitted with self lubricating bushings for long life performance and in combination with platform surfaces of ribbed anti-slip steel plate, the strength of Ravaglioli knuckle lifts out of Italy is unsurpassed.

ALEMLUBE 14512 QUICK CONNECT GREASE GUN COUPLER

The Alemlube 14512 is a patented lock-on grease gun coupler with a lever action and sliding sleeve that securely locks the coupler onto a grease nipple creating a leak proof seal. Hands-free greasing is now a reality!

Simply by depressing the trigger, attaching and releasing the coupler for a tight fit is a breeze and no hands are needed to align the coupler or keep it on the nipple.

Even at extreme angles, once the 14512 is attached, greasing can be performed at pressures of up to 10,000psi (690bar) - and can be forced to extreme angles on the grease nipple without leaking.

The 14512 works with all grease gun types - pneumatic, manual and battery, and accurately day in day out, in the field and in the workshop.





**354120
Samoa 3:1 Ratio
Oil Drum Pump**

- For medium size systems that involve hose reels and metered oil dispensing guns without simultaneous operation
- Flow rates of up to 35L/min
- Air inlet pressures between 40-140psi (3-10bar)
- 1/2" BSP(f) fluid outlet
- 1/4" BSP(f) air inlet
- Suits 205L drums

353120 also available but suitable for bulk tank application **\$969.00**

\$1,001.00



**454697
Samoa IBC Oil Storage
& Transfer Kit – Side Mount**

- 3:1 ratio pump facilitates flow rates of up to 18L/min
- Includes a 3:1 ratio pump, hose reel inclusive of 10m of hose, side mounting bracket & electronic oil meter
- IBC not included

454697C also available includes 1,000L IBC container, 3:1 ratio pump, dual pedestal hose reel with 10m of hose and electronic oil meter **\$5,079.00**

\$4,342.00



**AA205-2DG
Alemlube 205L 2 Drum
Oil Gantry**

- Steel bund with drain port & internal supports
- Moulded fibreglass mesh for drum support
- Alemlube 20m x 1/2" ID spring rewind oil hose reels
- Digital metered control guns, with drip trays
- Heavy duty 5:1 oil drum pump
- Tie down points for 205 drums
- 2" BSP drain port for bund included

\$6,887.00



**AA205-3DG
Alemlube 205L 3 Drum
Oil Gantry**

- Designed to be a cost effective, low maintenance oil delivery system
- Steel bund with drain port & internal supports
- Alemlube 20m x 1/2" ID spring rewind oil hose reels
- Digital metered control guns, with drip trays
- Heavy duty 5:1 oil drum pump
- Tie down points for 205 drums
- 2" BSP drain port for bund included

\$8,176.00



**454695
Samoa IBC Oil Storage
& Transfer Kit**

- 3:1 ratio pump, dual pedestal hose reel with 10m of hose, a top mounting bracket and electronic oil meter
- 3:1 ratio pump facilitates flow rates of up to 18L/min
- Electronic oil meter powered by quickly and easily replaceable AAA batteries
- IBC not included

454695C also available includes 1,000L IBC container, 3:1 ratio pump, dual pedestal hose reel with 10m of hose & electronic oil meter **\$4,922.00**

\$4,401.00



**348120
Samoa 5:1 Ratio
Oil Drum Pump**

- 5:1 ratio oil transfer pump designed to be used in 205L drums
- Maximum flow rate of up to 30L/min
- 3/4" BSP(f) fluid outlet
- 3/8" BSP(f) air inlet
- The ideal pump for dispensing high viscosity lubricants
- Powerful 90mm diameter air motor with a 100mm stroke
- Can service up to 8 reels

347120 also available as above but suitable for bulk tank applications **\$1,247.00**

\$1,298.00



ALEMITE 8080 SERIES HEAVY DUTY AIR, WATER, OIL & FUEL HOSE REELS

The Alemite 8080 Series hose reel is the first choice for many large mining and fleet service facilities. Its heavy duty construction and full flow fluid path allows for day in, day out reliability in many of Australia's most rugged workshops.

Key features include sealed for life bearings, a fully sealed spring rewind cassette and stainless steel roller guide assemblies covered by a lifetime warranty.

Available for a wide range of applications including the delivery of new oil, grease, engine coolant and diesel fuel, it can also be used for the reclamation of waste oil and other products.

The heavy duty hose reel design and construction means this is the reel for you.



555030 SAMOA 1" AIR OPERATED DIAPHRAGM PUMP

The Samoa 1" Air Operated Diaphragm Pump sets new standards of performance and efficiency created by its Directflo® technology.

New check valve design, improved air motor, top & lower fluid manifolds, orientable ports and one-piece diaphragms are just a few of the advanced features behind the Samoa 555030 performance. Higher suction capacity, reduced air consumption, shorter strokes and quiet operation all contribute to the 555030 resulting in extended diaphragm life, better resistance to abrasion, less stress on parts with minimum pulsation and vibration.

The Samoa 555030 offers maximum fluid flow with minimum air consumption, a no stalling, non-icing, reliable start up and multiple mounting options.



ALE-25BAH
Alemlube 1" Aluminium Diaphragm Pump

- 1" BSP(f) inlet/outlet
- Flow rates of up to 160L/min
- Suitable for the transfer of diesel fuel, gear oil, engine oil, waste oil, brake fluid, antifreeze
- Aluminium body and hytrel diaphragms
- Teflon and stainless steel models also available

ALE-20BAH also available with 3/4" BSP(f) inlet/outlet **\$2,036.00**

\$2,544.00



372400
Samoa Waste Oil Drainer/Extractor

- Premium quality and European engineering
- Drain bowl capacity of 20L
- Holding tank capacity of 100L
- Maximum working height of 2,000mm
- Minimum working height of 1,400mm
- Unique specially molded tray can be used to hold bolts, filters & washers
- Waste fluids can be pressurised or pumped out of the 100L capacity holding tank

\$1,164.00



372100
Samoa Mobile Waste Oil Drainer/Extractor

- Includes a 10 litres transparent chamber that can be used as vacuum reservoir and allows an immediate inspection of the extracted waste oil
- Venturi effect creates vacuum to suck waste oil out of vehicles dipstick by way of probe accessories
- Can be used as an autonomous unit, disconnected from air (once primed) Discharge hose is 1.6m

\$2,071.00



30101
Alemlube Mobile Waste Oil Drainer/Extractor

- Extracts and captures waste oil from crankcases, transmissions and differentials
- Draining hose length of 1" x 2,000mm
- Draining pressure of 14psi (1bar)
- 1/4" air inlet connection
- Clear inspection chamber capacity of 12L
- Collection bowl capacity of 20L, diameter of 420mm
- Holding tank capacity of 80L
- Suction hose specification of 1/2" x 2,000mm

\$1,507.00



10070
Alemlube Mobile Waste Oil Drainer/Extractor

- Collects waste oil from vehicle gear box or engine
- Air Consumption: 200L/min
- Air Inlet Pressure (for vacuum): 87-116PSI/6-8Bar
- Oil ejection pressure: 10-14PSI/0.7-1Bar
- Vacuum Degree: 0--14PSI/0--1Bar
- Tank Capacity: 70L
- Collect tray capacity: 16L
- Height: 1,100mm-1,680mm
- Working Temperature: 40-60°C (for engine oil)

\$660.00



ALE-15FPH
Alemlube 1/2" Air Operated Diaphragm Pump

- Flow rates of up to 45L/min
- 1/2" BSP(f) inlet/outlet
- Rugged bolted construction eliminates leaks and simplifies post maintenance reassembly
- Also suitable for the transfer of waste water, fuel, oil and some pesticides and herbicides

\$1,334.00



SAMOA ELECTRONIC ENGINE OIL METER

The Samoa 365534 electronic engine oil meter has been specifically designed to measure and dispense a range of synthetic and mineral oils.

With flow rates of up to 30L/min and a maximum working pressure of 1,450psi (100 bar), no calibration is required and the new pressure balanced spool valve is designed for unrestricted flow, superb control and comfortable use.

The latest innovative design features a trigger lock button that will lock the valve in the open position and also prevents accidental dispenses.

The oval gear meter component of the 365534 with its electronic 5-digit digital display powered by 2 x 1.5V AAA batteries offers high count precision and low flow resistance and registers the current amount dispensed displayed to the second decimal, a resettable partial totaliser (trip) and a total amount (total) can be alternatively selected.

The Samoa 365534 covers the needs of fluid dispensing ranging across truck, fleet, off-road, mining & construction and marine maintenance facilities.

ALEMLUBE SPILL CONTAINMENT SOLUTIONS

Alemlube addresses the need for safe workplace practices in all market sectors with a range of spill containment products suitable for most production facilities and applications.

Containing spills from IBC's, 205L drums and small containers of all capacities, the spill containers are manufactured in 100% polyethylene that will not rust or corrode, have excellent chemical compatibility and help to create a WH&S compliant workplace environment.

In addition to drum spill containers with non-slip removeable decks that are compatible with most forklifts & pallet trucks and under racking requirements, modular workfloors and ramps are available to create a safe storage centre that can be laid out in any shape to suit available floor space.



HOSE STORAGE & RETRIEVAL



505224N
Samoa 3/4" Fuel, Oil, Air & Water Hose Reel

- Heavy duty full metal double pedestal construction
- Hose capacity: 15m x 19mm ID
- Hose pressure rating 1,520psi (105bar)
- 3/4" BSP(f) inlet/outlet
- True 3/4" full flow shaft & ports
- Seven position outlet arm
- Full port nickel protected steel shaft

505232 also available with 20m x 12mm ID hose **\$2,508.00**

\$2,631.00



504250
Samoa 1/2" Twin Pedestal Oil Hose Reel

- Maximum working pressure of 2,300psi (160bar)
- 1/2" BSP(m) inlet/outlet
- Supplied complete with 15m x 1/2" ID R1 hose and 0.8m inlet hose
- Full 1/2" ID port, shaft and swivel
- Heavy duty double pedestal construction
- Large effective radial latching area
- Floor, wall, ceiling or tank mountable

\$1,625.00



S0600
Alemlube S Series Oxy-Acetylene Hose Reel

- 5/8" BSP inlet/outlet
- Maximum working pressure of 300psi (21bar)
- 15m x 6mm ID hose & 0.9m lead in hoses
- Ideal for back of ute or service vehicle use
- Adjustable spring tension & high flow swivel and fluid path

also available
SA630 Argon Gas hose reel **\$439.00**
SOP620 Oxy-Propane hose reel **\$679.00**

\$613.00



SA300N
Alemlube S Series Air Hose Reel

- 18m x 10mm ID hybrid polymer hose & 0.9m lead in hose
- High flow swivel and fluid path
- Detachable steel mounting bracket enables 180° hose reel rotation
- 3/8" BSP(f) inlet/outlet
- Dimensions: 490mm (L) x 448mm (H) x 228mm (W)

SA400N also available with 15m x 12mm hose **\$366.00**

\$344.00



HR90005
Alemlube EL Series 1" Air, Water & Fuel Hose Reel

- Reinforced steel frame provides maximum strength and stability
- Working pressure of up to 300psi (20bar)
- Includes 30m x 25mm ID rubber hose & hose stop
- 1.5mm thick robust drum with stiffening ribs and flange edges
- Reliable spring life of 20,000 cycles and positive ratchet lock design

HR90010 also available with 15m x 25mm ID hose **\$1,879.00**

\$2,275.00



508225
Samoa 1" High Volume Hose Reel

- Long-life heavy duty double arm design
- Supplied with 15m x 1" BSP(f) ID hose
- 1,250psi (86bar) hose pressure rating
- 1" port nickel coated steel shaft and swivel
- Zinc plated steel hose guide rollers
- Suitable for use with fuel, oil, air, water and waste oil
- Ideal for high volume applications

508925 also available bare reel with 15m x 1" ID hose capacity **\$2,445.00**

\$3,198.00



ALEMLUBE 51201N TYRE INFLATOR WITH GAUGE

The Alemlube 51201N Tyre Inflator with Gauge is heavy duty with an aluminium die cast body, impact absorbing bumpers and spiral protected air hose. Ideal for automotive, industrial and trade use, the 51201N incorporates slim ergonomic design features and is easy to use when inflating or deflating.

Highly accurate, the 51201N with magnified sight glass clearly indicates dual scale pressure reading of 0-150psi and 0-1,050Kpa.

Quality manufacturing and robust construction ensures dependable and trouble-free use day in, day out.

Also available is the Alemlube 51114 Digital Tyre Inflator designed with an LCD backlit digital display powered by two CR2032 batteries providing a life of 140 hours with normal use.



ALEMLUBE EL SERIES HR90000 HOSE REELS

The HR90000 Series Alemlube EL Series Air & Water Spring Rewind Hose Reels are available in low, medium and high pressure.

Medium pressure hose reels are supplied standard with S.A.E 100R1 at one wire braid hose suitable for air, water or oil application in auto and truck workshops. High pressure reels are supplied standard with S.A.E 100R2 at two wire braid hose suitable for grease applications.

With working pressures of 300-4,000psi and with adjustable arms, they allow for floor, wall or ceiling mounting according to needs.

The hose reel drum is sturdy and practical with stiffening ribs and flange edges.



20066N2
Alemlube LED
Work Light with Aircon
Gas Leak Detection

- 4W COB LED, 400lm on body
- 3W SMD LED, 100lm on top
- 80 CRI to illuminate true colours
- 3.7V 2200mAh Li-ion battery
- 3 hour main light run time
- 10 hour top light run time
- 28 hour top UV light run time
- 3.5 hour charge time
- 180° adjustable handle
- 3 strong magnets
- 2 foldaway hanging hooks

\$90.60



6603A
Alemlube 1L
Brake Cleaner Sprayer

- Large filling opening
- Safety valve at 36psi (2.5bar) with depressurisation option
- Easy tool free maintenance
- Ergonomic design
- Strong translucent bottle with level indicator
- Not suitable for use with acids

\$59.30



CR30060
Alemlube EL Series 240V
Electric Cable Reel - 15amp

- Supplied with 20m of 3 x 2.5mm² cable
- Maximum power when coiled is 1,600W, when uncoiled 3,200W
- Thermal overload protection
- Automatic and consistent speed control mechanism helps address WH&S concerns
- Australian Standard compliant in accordance with AS/NZ5 3000

CR30050 also available with Electric Cable Reel - 10amp **\$396.00**

\$432.00



BRP5216D
Alemlube Danger
Safety Barrier Reel

- Provides a temporary barrier to clearly identify dangerous areas
- Supplied complete with 16m x 52mm ID of durable red/white band with eyelet
- Automatic spring rewind mechanism
- Compact design suitable to mount in most workplace environments
- A must for addressing workplace and employee safety

BRP5216C also available complete with 16m x 52mm of durable yellow/black band with eyelet **\$405.00**

\$405.00



8828N2
Alemlube 20L Gear Oil
Drum Pump

- Capable of delivering up to 110mL per stroke
- Downtube extension and extra Rieke adaptor make the pump suitable for use with a variety of 20L drums
- Ideal pump for the transfer of engine, gear, diff and hydraulic oils
- Drainback nozzle holster ensures that excess oil ends up back in the drum
- UV stabilised long life hose ensures a long service life

O30010N also available delivers 80mL on the downstroke **\$52.70**

\$58.70



20084N
Alemlube Rechargeable
LED Slimline Work Light

- Utilises LED technology to provide incredible brightness via 50 LED lights with energy efficiency when working on your vehicles engine
- The flexible attachment clamps can be extended from a 117cm minimum to a maximum of 190cm
- The shatterproof polycarbonate lens combined with LED technology ensures longevity of life in your tough workshop environment

\$195.20



240V CHEMICAL & SOLVENT TRANSFER
205L DRUM PUMPS

Jessberger 240V drum pumps consist of a high performance, internally or externally ventilated universal motor, which is also available in an explosion-proof version and a pump tube that is suitable for your specific application. The pump tubes are available in Polypropylene for aggressive media as cleaning agents, acids and alkalis, up to 50 °C, PVDF (or highly aggressive media or when the medium temperature is between 50 °C and 90 °C, Aluminium for mineral oil products or Stainless steel 316Ti for flammable liquids such as petrol or solvents or thin liquid food.

The Jessberger pumps available from Alemlube are light weight, powerful and have been precision designed and manufactured in Germany.

THE ADBLUE® ADVANTAGE

AdBlue® is a non-toxic urea solution used to chemically reduce N²O (Nitrous Oxides) - emission from heavy duty diesel powered vehicles. It is neither explosive nor harmful to the environment and is classified under the minimum-risk category of transportable fluids.

AdBlue® is stored in a separate tank in the vehicle and the fluid is precisely injected into the engine's hot exhaust manifold, where the gases in the presence of a catalytic converter. The oxides formed at combustion are converted into harmless elementary nitrogen and water. This method is known as Selective Catalytic Reduction (SCR).





**51039
Alemlube 1" Auto Shut Off Diesel Nozzle**

- Automatically cuts off when a fuel tank is full
- Can operate with flow rates of up to 120L/min
- 1" BSP(f) swivel included
- Suitable for applications involving an electric diesel transfer pump

51037 also available with delivery rates of up to 60L/min **\$308.00**

\$370.00



**501A
Alemlube Rotary Action Drum Pump**

- Suitable for the transfer of diesel, petrols, kerosene, lube oil and machine oil
- 2" BSP bung adaptor
- Anti static fuel hose
- Delivery rates of up to 18L/min or 0.26L per rotation
- Can syphon and transfer fuels and lubes in reverse
- Includes 2.2m of farm tank hose, bung adaptor, rubber gasket, a four chamber rotor assembly, spout and spout holster

\$190.50



**52004A
Alemlube 12V High Volume Diesel Drum Pump**

- Flow rates of up to 80L/min
- 1" BSP(f) inlet/outlet
- Telescopic down tube suits fuel tanks up to 1,000mm deep
- Includes an automatic shut off nozzle
- Self priming vane pump with sintered steel rotor and acetyl resin vanes
- Duty cycle of 30 minutes on / 30 minutes off
- Dry prime of 2m

52004 also available with manual nozzle **\$1,294.00**

\$1,573.00 



**5060AN
Alemlube Heavy Duty Hi-Flo Refuelling Drum Pump**

- Low torque, high volume easy to use pump delivers up to 110L/min
- Supplied complete with 2.6m of UV and fuel resistant hose, spout, in built spout holster, 3-piece downtube, heavy duty bung adaptor
- Suitable for the transfer of diesel fuel, petrol, light oils up to SAE30 and kerosene

5080AN also available with filter **\$765.00**

\$487.00 



**52000
Alemlube 12V Diesel Refuelling Tank Kit**

- Capable of flow rates of up to 50L/min
- Includes 4m of antistatic fuel delivery hose, 2m of battery cable, a stainless steel & brass fuel filter and a manual nozzle
- Maximum head capacity of 15m
- Self priming vane pump includes a built-in bypass
- Duty cycle of 30 minutes on, / 30 minutes off
- Suction capacity of up to 2m

5200A also available in 24V **\$760.00**

\$590.00



**51040
Alemlube 1" Hi-Flo Auto Shut Off Diesel Nozzle**

- High speed, reliable & robust automatic nozzle
- Maximum flow rate of 140L/min
- 1" BSP(f) hot stamped brass swivel
- 3-speed lever with removable latch pin
- 3-position stay open latch
- Soft PVC cover/scuff guard
- Suitable for dispensing petrol, diesel fuel and bio diesel up to B5

\$393.00

ALEMLUBE SERVICE VEHICLES

In the Pilbara, out at Roxby Downs and in the Bowen Basin, Service Vehicles are taking workshop services directly to vehicles and mobile equipment operating in the field.

For over a decade, Alemlube has supplied a good number of the Service Vehicles OEM's with a wide range of oil, diesel fuel, grease and waste oil transfer and metering equipment and currently Alemlube products and after sales service is a part of that programme.

Today, Alemlube products are predominantly Samoa pumps, hose reels and control valves which operate successfully all over the country plus in parts of Africa helping big and not so big miners keep their valuable plant & machinery operative and productive.




B.SMART FUEL MANAGEMENT SOLUTIONS

Piisi B.SMART is an intuitive and simple Smart Fuel Management System comprising hardware and software driven by Bluetooth technology to easily monitor and manage diesel fuel usage in a fleet of any size, large or small

- Utilising a smart device App for drivers and a Web App on the Cloud for fleet managers, the new Piisi Smart Fuel Management System with its integrated software is fully managed in the Cloud meaning that no complicated PC installation is required to get you up and running
- B.SMART allows you to manage your fleet from anywhere and to monitor all fuel transactions in real-time
- Your Flexible and Modern Fuel Management Solution





Alemlube Lockable Diesel Refuelling Storage and Dispensing Kits

- Flow rates of up to 50L/min
- Heavy duty, robustly constructed polyethylene tank
- Built in nozzle holster
- Unique user friendly design with lockable lid to aid fuel and dispensing kit security
- Dispensing kit consists of a 12V pump, 4m antistatic fuel delivery hose, 2m battery cables and automatic nozzle
- Recesses for tie down straps on the tank aid handling
- Forklift lift points and tie down capability

PRODUCT NUMBER	CAPACITY	FLOW RATE	\$
L10040PA	100L	50L/min	1,227.00
L20040PA	200L	50L/min	1,315.00
L45040PA	450L	50L/min	1,798.00
L60040PA	600L	50L/min	1,958.00



LOCKABLE DIESEL FUEL STORAGE & DISPENSING

Alemlube has addressed the need for user friendly, transportable lockable diesel fuel storage and dispensing kits with the introduction of the new lockable range of 600L, 450L, 200L & 100L polyethylene tank/dispensing kits.

Covered by the comprehensive Alemlube 2 year warranty, the kits comprise of a 12V pump manufactured in Italy, 4m antistatic fuel delivery hose and automatic nozzle. Capable of delivery rates of up to 50L/min, each capacity kit is available with the addition of a fuel meter. Pallet lift points and tie down strap recesses greatly assist in handling and transportation.

Already in use by earth moving contractors, road builders, in industry, agriculture and minesites, the Alemlube lockable diesel fuel storage and dispensing kits represent mobile refuelling at its best.



Stores advertised on page one of this catalogue are independent businesses. Every effort has been made to ensure that advertised stock is available, but due to factors beyond the control of Alemlube Pty Ltd not all products advertised in this catalogue are available at all stores. Pricing for the products are special prices available through to 12th of December 2022. Regular prices vary from store to store. The catalogue pricing is calculated in good faith as the average regular price at the time of preparation. Alemlube Pty Ltd will do everything possible, within reason, to maintain stocks of advertised products but cannot be responsible for unforeseen shortfalls beyond their control.

All products are covered by a 2 year warranty (unless otherwise stated) and with the aid of our sixty five strong nationwide Authorised Agent Network, technical support for all Alemlube products featured in this catalogue will never be far away. E.&O.E. Copyright 2022. Reproduction in whole or part is prohibited without written approval. All prices shown include GST. Freight charges may be applicable and may vary from region to region.